



GLAZE X-TENDER

Additive For Water Based Glazes
(No. 1140)

Applications:

**Extending The Drying
& Working Time Of
Water Based Glazes**

Features & Benefits:

For Interior Glazes

**Increases the Open
Time (Working Time)
Up To 45 Minutes !**

**Does Not Reduce
The Viscosity Of The
Glaze When Added**

Product Description: XIM Glaze X-Tender is an additive for water based Glazes. It extends drying and working time of the glaze up to 45 minutes or more. Add the Glaze X-Tender up to one (1) pint per gallon of Glaze. A great advantage of the glaze X-Tender is that it does not lower the viscosity of the Glaze.

Product Preparation: XIM Glaze X-Tender is ready to use from the can. Stir or shake well before using.

Note: Keep from freezing. Keep the containers tightly closed when not in use. Store at room temperature.

Packaging Data: XIM Glaze X-Tender #1140

Gallons	- 6 per carton	#11401
Quarts	- 4 per carton	#11402

Technical Service Information:

For further information about this or any other XIM product, contact our Technical Service Staff toll free at (800) 262-8469.

Limited Warranty: This product is made to the highest standards in order to provide you with consistently optimum results. If this product fails to perform as specified herein, XIM will furnish an equivalent amount of replacement XIM product, or will refund the purchase price upon proof of purchase. XIM will not be liable for any indirect or consequential damages. There are thus no warranties of fitness or merchantability beyond that provided above. This warranty does not include labor or cost of labor for application or removal of any paint or primer. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

XIM When Ordinary Primers Are Not Enough !™

XIM Glaze X-Tender (1140)

Clean-Up: Clean equipment with soap and water immediately after use.

First Aid: If swallowed, do not induce vomiting.. **CALL A PHYSICIAN IMMEDIATELY.** In case of eye contact, flush with plenty of water. Avoid prolonged skin contact and avoid breathing mist or sanding dust if sanded.

For additional information see the Material Safety Data Sheet (MSDS) for this product.

Physical/Chemical Data: Glaze X-Tender

Wt. Per Gal.	8.5 lb
Volatile by weight	97 %
Viscosity	110 - 120 KU
Dry to touch:	Extends Dry Time 45 min to 1 hour
Gloss	Does not affect Gloss of the Glaze
Color	Does not add to or detract from the color of the glaze
Recommended Use	Up to one Pint per gallon of glaze
VOC	less than 8 g/l

XIM Products, Inc., 1169 Bassett Road, Westlake, Ohio 44145 (800) 262-8469

10/20/98