



TECHNICAL DATA

The Must For Rust

DESCRIPTION

Recommended uses:

THE MUST FOR RUST

STOPS RUST & PROTECTS METAL!

The proprietary (water-based) formulation penetrates into every void of a metal surface and dissolves rust/oxidation through chemical action. Then tiny, rust-inhibiting crystals are formed and become integral with the surface molecules of the metal to resist future rusting. Removes blueing on firearms instantly.

IMPORTANT:

Always test first on an inconspicuous area. For best results apply in ambient temperature of 70F or above. On metal, maintain wet solution on surface to remove rust. Once the rust is dissolved, rinse or wipe the surface, and wait one hour or more before painting. Do not allow remover to dry on painted surfaces. For improved paint adhesion on clean metal surfaces, dilute remover 50/50 with water, apply solution, and rinse or wipe the surface. To use as a rust inhibitor on unpainted metal, allow the remover to dry on the surface after the rust is dissolved. The remover will then protect bare metal against rust for up to 12 months. MFR will etch concrete and turn the surface white. Recommend covering concrete with a plastic drop cloth for protection.

DO NOT USE ON MARBLE.

**COVERAGE: 50sq.ft./quart;
200sq.ft./gallon.**

COLOR: Green

PACKAGING/CONTAINERS:
Available in 8oz., 32oz., 1gal., 5gal., 55gal.

APPLICATION

Directions for use:

Remove oil and grease from the metal to be treated. Rinse the metal to break the surface tension and wash away loose dirt. Apply the remover by brush, spray or by dipping. Use plastic, glass or stainless steel containers. Disassemble units composed of moveable parts before cleaning. Clean parts and allow to dry before reassembling

Dissolving rust from iron or steel:

Apply the remover as required to penetrate the rust. Chemical action begins at once. Cleaning time will vary according to the rust. Medium to light rust will be dissolved in 30 minutes or less, while heavier deposits may require a second application.

Aluminum/Chrome:

Apply the remover to wet surface. Allow time to clean, then rinse away with clean water, and buff dry with a cloth.

Galvinizing:

Where surface is unbroken, treat as suggested for aluminum. Where rust is showing at the surface, treat as for iron or steel. New galvinizing is properly prepared for painting by applying the remover and allowing to dry on surface.

Bathroom/Shower/Toilet Cleaner:

Dissolves most calcium, lime and other hard water stains on porcelain, tile, fiberglass, and glass. Spray remover directly onto surface, let sit for 5 minutes. Agitation with brush will speed penetration. Rinse away with water when stain is removed.

Auto Cooling System:

Removes oxides and rust when circulated in the system. When cleaning action is complete, flush system with fresh water and refill with coolant.

CAUTION

Eye and skin irritant. In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. Material Safety Data Sheet available.

DO NOT MIX THIS PRODUCT WITH ANY OTHER CHEMICALS.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA

Physical Data:

CONTAINS: Phosphoric acid in a water-based solution.

FLASH POINT: N/A

SHELF LIFE: N/A

VOC: 1

**FOR EMERGENCY CALL
CHEMTREC (800-424-9300)
INTERNATIONAL (703-527-3887)
(COLLECT CALLS ACCEPTED)**

AVAILABILITY

Krud Kutter brand products can be found in the paint department of most home improvement, hardware, and paint stores in the US and CANADA. For a list of retailers please:
**visit www.krudkutter.com or
call 800-466-7126.**

Supreme Chemicals of GA, INC.
1535 Oak Industrial Ln., Ste. B
Phone: 770-888-8827
Fax: 770-888-8835
www.krudkutter.com
sales@krudkutter.com
Got Krud...Get Krud Kutter!